

TAPS & SPLITTERS

MS4/8 MS4/12

Passive splitter conceived to distribute on 2 columns of the 4 IF-SAT polarizations.

ITEM CODE	MS4/8	MS4/12
NUMBER OF INPUTS	4	
NUMBER OF OUTPUTS	8	12
FREQUENCY BAND	5 - 2200 MHz	
SIGNAL LOSS	- 4 dB	- 6 dB
ISOLATION BETWEEN INPUTS	> 40 dB	
ISOLATION BETWEEN OUTPUTS	> 20 dB	
RETURN LOSS	> 20 dB	
SUPPLY CURRENT MAX.	1.000 mA	
DIMENSIONS	85 x 95 x 27	95 x 95 x 27




MD4/4-10 MD4/4-15 MD4/4-20

Passive taps conceived to derive in 4 polarizations plants.

ITEM CODE	MD4/4-10	MD4/4-15	MD4/4-20
NUMBER OF INPUTS	4		
NUMBER OF OUTPUTS	4		
NUMBER OF TAPS	4		
FREQUENCY BAND	900 - 2200 MHz		
THROUGH LOSS	- 0,7 dB		
TAP LOSS	- 10 dB	- 15 dB	- 20 dB
ISOLATION BETWEEN INPUTS	> 40 dB		
RETURN LOSS	> 15 dB		
SUPPLY CURRENT MAX.	1.000 mA		
DIMENSIONS	116 x 86 x 27		



F250L
Connection F male - F male



RCS75
75 Ohm insulated dummy load