







# Series DR1

## 1-way vertical taps Band 5... 2.400Mhz

-  **DC pass between output and input**
-  **High isolation between outputs**
-  **High performance with very low insertion loss**
-  **Installation in any junction box**
-  **Ready for wall mounting**
-  **Die-cast alloy body**



**Wideband taps with F connectors.** Available with different levels of attenuation at the tap output.

The products in this series are manufactured from die cast Zamak alloy to ensure high shielding and are fitted with a grounding screw.



MODEL		DR1-10	DR1-15	DR1-20	DR1-25
TAPS	n°	1	1	1	1
<b>TAP LOSS</b>					
5-40MHz	dB	10	15	20	25
40-1000MHz	dB	10	15	20	25
1000-2050MHz	dB	10	15	20	25
2050-2400MHz	dB	10	15	20	25
<b>INSERTION LOSS (IN-OUT)</b>					
5-40MHz	dB	2	1,5	1,5	1,5
40-1000MHz	dB	2	1,5	1,5	1,5
1000-2050MHz	dB	3	2,6	2,6	2,6
2050-2400MHz	dB	3	2,8	2,8	2,8
<b>ISOLATION (OUT-TAP)</b>					
5-40MHz	dB	18	18	18	18
40-1000MHz	dB	25	25	25	28
1000-2050MHz	dB	22	22	22	25
2050-2400MHz	dB	20	20	20	25
<b>RETURN LOSS</b>					
5-40MHz	dB	10	10	10	10
40-1000MHz	dB	12	12	12	12
1000-2050MHz	dB	11	11	11	11
2050-2400MHz	dB	10	10	10	10
<b>GENERAL FEATURES</b>					
IMPEDANCE	Ohm	75			
DIMENSIONS	mm	49x35x28	49x35x28	49x35x28	49x35x28