







Series DR2

2-way vertical taps Band 5... 2.400Mhz

-  **DC pass between output and input**
-  **High isolation between outputs**
-  **High performance with very low insertion loss**
-  **Installation in any junction box**
-  **Ready for wall mounting**
-  **Die-cast alloy body**



Wideband taps with F connectors. Available with different levels of attenuation on the tap outputs.

The products in this series are manufactured from die cast Zamak alloy to ensure high shielding and are fitted with a grounding screw.



MODEL		DR2-10	DR2-15	DR2-20	DR2-25
TAPS	n°	2	2	2	2
TAP LOSS					
5-40MHz	dB	10	15	20	25
40-1000MHz	dB	10	15	20	25
1000-2050MHz	dB	10	15	20	25
2050-2400MHz	dB	10	15	20	25
INSERTION LOSS (IN-OUT)					
5-40MHz	dB	4,3	2,5	2,0	1,5
40-1000MHz	dB	5,0	3,0	2,5	1,5
1000-2050MHz	dB	5,5	3,5	3,5	3,0
2050-2400MHz	dB	5,7	3,8	3,8	3,3
ISOLATION (OUT-TAP)					
5-40MHz	dB	25	25	25	30
40-1000MHz	dB	20	25	25	28
1000-2050MHz	dB	20	22	22	25
2050-2400MHz	dB	20	20	20	25
RETURN LOSS					
5-40MHz	dB	10	10	10	10
40-1000MHz	dB	12	12	12	12
1000-2050MHz	dB	11	11	11	11
2050-2400MHz	dB	10	10	10	10
GENERAL FEATURES					
IMPEDANCE	Ohm	75			
DIMENSIONS	mm	49x35x28	49x35x28	49x35x28	49x35x28