







# SP2

## 2-way vertical splitter Band 5... 2.400Mhz

-  **DC pass through on all outputs**
-  **High isolation between outputs**
-  **High performance with very low insertion loss**
-  **Installation in any junction box**
-  **Ready for wall mounting**
-  **Die-cast alloy body**



### Wideband splitter with F-connectors.

The **DC pass** from the outputs to the input is directional thanks to **internal diodes**.

The products in this series are manufactured from die cast Zamak alloy to ensure maximum immunity to environmental interference.

**5**  
WARRANTY YEARS

MODEL		SP2
OUTPUTS	n°	2
<b>INSERTION LOSS (IN-OUT)</b>		
5-40MHz	dB	4,5
40-1000MHz	dB	5
1000-2050MHz	dB	5,8
2050-2400MHz	dB	6
<b>ISOLATION (OUT-OUT)</b>		
5-40MHz	dB	16
40-1000MHz	dB	20
1000-2050MHz	dB	20
2050-2400MHz	dB	20
<b>RETURN LOSS</b>		
5-40MHz	dB	10
40-1000MHz	dB	12
1000-2050MHz	dB	12
2050-2400MHz	dB	10
<b>GENERAL FEATURES</b>		
IMPEDANCE	Ohm	75
DIMENSIONS	mm	49x35x28