

SP3

3-way vertical splitter Band 5... 2.400Mhz

- ✓ **DC pass through on all outputs**
- ✓ **High isolation between outputs**
- ✓ **High performance with very low insertion loss**
- ✓ **Installation in any junction box**
- ✓ **Ready for wall mounting**
- ✓ **Die-cast alloy body**



Wideband splitter with F-connectors.

The **DC pass** from the outputs to the input is directional thanks to **internal diodes**.

The products in this series are manufactured from die cast Zamak alloy to ensure maximum immunity to environmental interference.

5
WARRANTY YEARS

| MODEL | | SP3 |
|--------------------------------|-----|----------|
| OUTPUTS | n° | 3 |
| INSERTION LOSS (IN-OUT) | | |
| 5-40MHz | dB | 7 |
| 40-1000MHz | dB | 8 |
| 1000-2050MHz | dB | 10 |
| 2050-2400MHz | dB | 11 |
| ISOLATION (OUT-OUT) | | |
| 5-40MHz | dB | 16 |
| 40-1000MHz | dB | 20 |
| 1000-2050MHz | dB | 20 |
| 2050-2400MHz | dB | 20 |
| RETURN LOSS | | |
| 5-40MHz | dB | 10 |
| 40-1000MHz | dB | 12 |
| 1000-2050MHz | dB | 12 |
| 2050-2400MHz | dB | 10 |
| GENERAL FEATURES | | |
| IMPEDANCE | Ohm | 75 |
| DIMENSIONS | mm | 49x35x28 |